

STANDARD SPECIFICATION SHEET

POTASSIUM ACETATE

Chemtech Product Code 40

<p>Formula: Synonyms:</p> <p>CAS No: EINECS No:</p>	<p>CH₃COOK</p> <p>127-08-2 204-822-2</p>		
<p>Specification:</p>		<p>Industrial grade</p>	<p>Food Grade</p>
	<p>Purity, %:</p> <p>PH:</p> <p>Chlorides, %:</p> <p>Fe, %:</p> <p>Loss on heating, %:</p> <p>As, %:</p> <p>Sulfate, %</p> <p>Mg, %</p> <p>Heavy metal (Pb), %</p> <p>Al, %</p> <p>Hg, %</p> <p>Na, %</p>	<p>99.0-100.5</p> <p>7.5-8.5</p> <p>0.05 max.</p> <p>0.001 max.</p> <p>1.0 max.</p> <p>0.0004 max.</p> <p>0.01 max.</p> <p>0.01 max.</p> <p>//</p> <p>//</p> <p>//</p> <p>//</p> <p>//</p> <p>//</p>	<p>90.0-100.5</p> <p>7.5-8.5</p> <p>0.01 max.</p> <p>0.001 max.</p> <p>1.0 max.</p> <p>0.0004 max.</p> <p>//</p> <p>//</p> <p>0.0001 max.</p> <p>0.0004 max.</p> <p>0.0001 max.</p> <p>0.5% max.</p>
<p>Use:</p>	<p>Potassium Acetate is used for the manufacture of antibiotics, potassium penicillinate, and in solutions for haemodialysis and peritoneal dialysis. In addition, it can be used as a textile conditioner, a polymerization catalyst and as a catalyst in the production of polyurethane foams and carbon black. It is also used as a dehydrating agent, ad runway de-icing fluid or oil-drilling fluid additive. It is also used in food and feed industry.</p>		
<p>Packing:</p>	<p>25kg bag. 1 Fcl=25mt/22mt (loose/palletized)</p>		